

## SPECIFICATIONS

<b>WEIGHT (SJKB-33N)</b> .....	14,500# (6577kg)
<b>WORK HEIGHT (SJKB-33N)</b> .....	39' (11.89m)
<b>RAISED PLATFORM HEIGHT(nominal)(SJKB-33N)</b> .....	33' (10.06m)
<b>STOWED HEIGHT</b> .....	6' 7" (2.0m)
<b>OVERALL WIDTH (SJKB-33N)</b> .....	48" (1.22m)
<b>STOWED LENGTH (SJKB-33N)</b> .....	14' 4" (4.36m)
<b>PLATFORM CAPACITY (Unrestricted)</b> .....	500# (227kg)
<b>PLATFORM SIZE (SJKB-33N, -33i, -40i)</b> .....	30.00" x 48.00" (.76m x 1.22m)
<b>ELECTRICAL SYSTEM</b> .....	48 Volts DC
<b>GRADABILITY</b> .....	30%
<b>TURRET ROTATION (SJKB-33N)</b> .....	355° (Non-continuous)
<b>TIRE SIZE (SJKB-33N)</b> .....	27.5" x 7.5" x 15" Solid Urethane

### STANDARD EQUIPMENT

- 4 Foot Hydraulically Controlled Boom Jib
- Variable Speed Drive and Function Controls
- In-Line Elevating Assembly
- Continuous Drive and Steer Directional Sensing
- Electrical Dynamic Braking System
- Two Spring-Applied Hydraulically-Released Parking Brakes
- ANSI and CSA Standards Compliance

