

DC Electric Scissor Lifts

Specifications	SJIII 3226
A Work Height	9,9 m
B Raised Platform Height	7,9 m
C Lowered Platform Height	1,1 m
D Overall Width	0,8 m
E Overall Length	2,3 m
F Stowed Height (Rails Up)	2,2 m
G Stowed Height (Rails Down)	1,9 m
H Platform Width (Inside Dimension)	0,7 m
I Platform Length (Inside Dimension)	2,1 m
Extension Deck (Roll Out)	0,9 m
Ground Clearance (Stowed)	8,6 cm
Ground Clearance (raised)	1,9 cm
Wheelbase	1,8 m
Weight	1890 kg
Gradeability	30%
Turning Radius (Inside)	1,3 m
Turning Radius (Outside)	2,8 m
Lift Time (With Rated Load)	53 sec
Drive Speed (Stowed)	3,1 km/h
Drive Speed (Raised)	1,1 km/h
Maximum Drive Height	Full Height
Capacity (Overall)	227 kg
Maximum # of Persons	2

STANDARD FEATURES

- Drivable at full height
- Variable speed, rear two wheel hydraulic drive
- Dual holding brakes
- Proportional controls for drive & lift functions
- 0,9 m roll out extension deck
- 24V DC power source
- Low voltage battery protection
- Analog control system
- Colour coded and numbered wiring system
- 30% gradeability
- Solid rubber, non-marking tyres
- Pothole protection system
- Wiring for AC outlet on platform
- Tilt alarm with drive & lift cut-out
- Overload sensing system
- Lowering warning system
- Operator horn
- Hinged railing system (3226 only)
- Half height spring hinged gate
- Lanyard attachment points
- Forklift pockets and tie down/lift lugs

