

SPECIFICATIONS

WEIGHT (SJKB-40i, -40C)	12,800# (5806kg)
WORK HEIGHT (nominal)(SJKB-40i, -40C)	46' (14.02m)
RAISED PLATFORM HEIGHT (nominal)(SJKB-40i, -40C)	40' (12.19m)
STOWED HEIGHT	6' 7" (2.0m)
OVERALL WIDTH (SJKB-33C, -40C)	5' 10" (1.78m)
STOWED LENGTH (SJKB-40i, -40C)	18' 3" (5.56m)
PLATFORM CAPACITY (Unrestricted)	500# (227kg)
PLATFORM SIZE (SJKB-33N, -33i, -40i)	30.00" x 48.00" (.76m x 1.22m)
PLATFORM SIZE (SJKB-33C, -40C)	30.00" x 66.00" (.76m x 1.68m)
ELECTRICAL SYSTEM	48 Volts DC
GRADABILITY	30%
TURRET ROTATION (SJKB-33i, -33C, -40i, -40C)	365° (Non-continuous)
TIRE SIZE (SJKB-33C, -40C) (Lugged)	30" x 10" x 16.5 Air Filled

STANDARD EQUIPMENT

- 4 Foot Hydraulically Controlled Boom Jib
- Variable Speed Drive and Function Controls
- In-Line Elevating Assembly
- Continuous Drive and Steer Directional Sensing
- Electrical Dynamic Braking System
- Two Spring-Applied Hydraulically-Released Parking Brakes
- ANSI and CSA Standards Compliance

