

**Table 1-1  
SPECIFICATIONS**

Model	Turning Radius		Work Height	Raised Height	Lowered Height	O/A Width	O/A Length	Capacity	Platform Size	Tire Size	Travel Speed			Weight w/o Batteries	Cubic Feet
	I.D.	O.D.									High MPH	Low MPH	Lift Speed Sec.		
SP16-33	61"	113"	22'	16'	39"	33"	81"	750	30" x 78"	*	2	.75	30	2,250	124
SP16-44	55"	116"	22'	16'	39"	44"	81"	1,000	42" x 78"	*	2	.75	30	2,350	94
SPL16-46	53"	118"	22'	16'	40"	46"	81"	1,000	42" x 78"	**	2	.75	30	2,500	99
SP16-56	53"	130"	22'	16'	40"	56"	81"	1,000	54" x 78"	*	2	.75	30	2,450	120
SPL16-60	51"	132"	22'	16'	41"	60"	81"	1,000	54" x 78"	***	2	.75	30	2,600	131
†SP21-33	61"	113"	27'	21'	45"	33"	81"	1,000	30" x 78"	*	2	.75	35	2,550	133
SP21-44	55"	116"	27'	21'	45"	44"	81"	750	42" x 78"	*	2	.75	35	2,650	107
SPL21-46	53"	118"	27'	21'	46"	46"	81"	650	42" x 78"	**	2	.75	35	2,800	114
SP21-56	53"	130"	27'	21'	47"	56"	81"	1,000	54" x 78"	*	2	.75	35	2,700	141
SPL21-60	51"	132"	27'	21'	47"	60"	81"	1,000	54" x 78"	***	2	.75	35	2,900	151
††SPL21-62	50"	133"	27'	21'	50"	62"	93"	1,000	54" x 78"	****	2.25	.75	35	3,550	187
††SP25-44	55"	116"	31'	25'	50"	44"	81"	750	42" x 78"	*	2	.75	40	3,030	117
††SPL25-48	53"	118"	31'	25'	51"	48"	81"	750	42" x 78"	***	2	.75	40	3,330	130
†††SPL26-62	50"	133"	32'	26'	55"	62"	93"	1,000	54" x 78"	****	2.25	.75	40	3,850	204
SP21-33CT	61"	113"	27'	21'	45"	33"	92"	750	30" x 78"	*	2	.75	35	3,650	150
SP25-44CT	55"	117"	31'	25'	50"	44"	92"	750	42" x 78"	*	2	.75	40	4,280	132
SPL26-66	48"	135"	32'	26'	55"	66"	93"	750	42" x 78"	****	2.25	.75	40	3,850	216

†Maximum drive height — 14'

††Maximum drive height — 15'

†††Maximum drive height — 18'

\*16 x 5.00 x 8" Solid Rubber

\*\*16 x 6.50 x 8" Solid Urethane Filled

\*\*\*18 x 9.5 x 8" Solid Urethane Filled

\*\*\*\*26 x 12 x 12" Solid Urethane Filled

NOTE: All Units Standard Less Batteries

Specifications subject to change without notice

### STANDARD FEATURES

- Heavy-duty railing with mid-rail and 6" toe-boards
- Key switch console assembly on the platform
- Trunnion mounted telescoping cylinders
- 2 speed dual wheel hydraulic drive
- Parking brake
- Climbs 30% grades
- Slide-out "works in-a-drawer" electrical/hydraulic componentry
- Color coded wiring
- Engineered for simplified service
- Fork lift pockets on both ends for easy transport
- Working heights to 32' 1,000 lbs capacity
- ANSI compliance Certified by Pittsburgh Testing Laboratory.\*
- Audible "beeper" down signal
- Hourmeter

### OPTIONAL ACCESSORIES

- 6' Crank Out Extension††††
- 3' Slide Out Extension††††
- 3' Roll Out Extension††††
- Flashing Light
- Back Up Horn
- 115V Motor Generator
- Fold-down Railing System
- Retractable Rails for 3' Extension
- Retractable Rails for 6' Crank Out
- AC Outlet on Platform
- Stabilizers (not available with 26 x 12 x 12 tires)
- Tool Tray 34" Long
- Battery Kit (4-250 A/H)
- High Speed Wheel Motors (Increases travel speed to 3 MPH)
- EE Rating
- Entrance Gate

††††Platform capacities are reduced when using optional platform extensions.

Manufactured in conformance with ANSI A92.6 dated 1979.

\*As interpreted by Snorkel-Economy.