




Genie Self-Propelled Scissor Lifts

A TEREX BRAND

GS-4069 RT

Specifications



Models	GS-4069 RT
Measurements	Metric
Working height maximum*	14.02 m
A Platform height maximum	12.2 m
Drive height	12.2 m
B Platform height - stowed	1.65 m
C Platform length - outside	2.79 m
extended	3.96 m
Slide-out platform extension deck	1.52 m
D Platform width - outside	1.6 m
Toeboard height	0.15 m
E Height - stowed**	2.74 m
rails lowered	2.08 m
A Length - stowed	3.12 m
platform extended	4.5 m
with outriggers	3.76 m
G Width	1.75 m
H Wheelbase	2.29 m
A Ground clearance - center	0.24 m

Productivity

Maximum platform occupancy***	3
Lift capacity	363 kg
Extension deck capacity	136 kg
Drive speed - stowed	5.6 km/h
Drive speed - raised	0.5 km/h
Gradeability - stowed****	35%
Maximum outrigger leveling:	
front/back uphill	5.3° / 4.2°
side to side	11.7°
Turning radius - inside	2.11 m
Turning radius - outside	4.6 m
Raise/lower speed	69/46 sec
Controls	proportional
Drive	four wheel
Tires - rough terrain	30x66 cm

Power

Power source	Kubota DF-972 gas/LPG 29 hp Kubota D-1105 Diesel 24.8 hp Perkins 403D-11 Diesel 26 hp
Fuel tank capacity	37.9 L
Hydraulic system capacity	68.1 L

Weight*****

	4,647 kg
with outriggers	5,039 kg

* The metric equivalent of working height adds 2 m to platform height.

** Based on RT tires; deduct 2 in (5.8 cm) for turf and non-marking tires.

*** CE/AUS markets: GS™-4069 are limited to 2 person platform occupancy when used outdoors.