

# SPECIFICATIONS

<b>Working Height</b>	20.80m	68ft 6in
<b>Platform Height</b>	18.80m	62ft
<b>Working Outreach</b>	12.80m	42ft
<b>Slew</b>	360°	
<b>Fly-Boom Arc</b>	150°	
<b>Width</b>	2.27m	7ft 5in
<b>Height</b>	2.15m	7ft
<b>Length - Stowed</b>	5.30m	17ft 5in
<b>- Overall</b>	6.65m	21ft 10in
<b>Minimum Weight - (2x4)</b>	6,500kg*	14,330lbs*
<b>- (4x4)</b>	6,500kg*	14,330lbs*
<b>Turning Radius - Outside</b>	4.00m	13ft
<b>Platform Rotation</b>	100°	
<b>Platform Capacity</b>	225kg	500lbs
<b>Platform Size</b>	1.80m x 0.85m	5ft 11in x 2ft 9in
<b>Drive Speed - (2x4)</b>	4.5kph	2.8mph
<b>- (4x4)</b>	6.6kph	4.1mph
<b>Gradeability</b>	30% (2x4)	45% (4x4)
<b>Power System - (2x4)</b>	Battery Only	
	Bi-Energy (Battery & Diesel) Kubota 722 (18Hp)	
<b>- (4x4)</b>	Diesel Only Kubota 1505 (32Hp)	